

Data Sheet

ProPride Series

of Solid Vinyl Siding



Unconditional Quality With Exceptional Value.

Illustration	Description/Packaging	Colors/Color Nos.	
<p>20PP245 ___</p>	<p>Double 4.5" Natural Cedar Woodgrain Finish Length 12' -2" 22 Panels/Carton 2 Sq./Carton Carton Weight: 75 lbs.</p>	White Birch (02) Classic Sand (11) Warm Sandalwood (17) Sunny Maize (22)	Summer Wheat (26) Harbor Stone (44) *Victorian Slate (67) *Terra Clay (69)

Illustration	Description/Packaging	Colors/Color Nos.	
<p>20PP245DL ___</p>	<p>4.5" Dutchlap Natural Cedar Woodgrain Finish Length 12' 2" 22 Panels/Carton 2 Sq./Carton Carton Weight: 75 lbs.</p>	White Birch (02) Classic Sand (11) New Linen (13) Warm Sandalwood (17) Sunny Maize (22) Summer Wheat (26) Autumn Taupe (28)	Harbor Stone (44) *Vintage Sage (55) *Wicker Beige (65) *Victorian Slate (67) *Terra Clay (69) *Charcoal Grey (84)

*Premium colors made with Armor Coat UVA™

ProPride™ Vinyl Siding

RMC Vinyl Siding passes or exceeds all industry standards per ASTM D3679.

Product Test Data

Thickness.....	.040" ± .001"	Impact Resistance.....	Passes per ASTM D3679
Specific Gravity.....	1.45	Surface Distortion @ 140°F.....	0
Tensile Strength (PSI).....	7,000	Fire Rating.....	Class A
Tensile Modulus (PSI).....	400,000	Flame Spread Index.....	20.0
IZOD Impact Strength @ 32°F.....	Passes per ASTM D3679	Smoke Developed.....	275
Heat Deflection Temp. @ 264 PSI.....	163°F	Fuel Contribution.....	0
Coefficient of Linear Expansion.....	2.69 x 10 ⁻⁵	Average Time Of Burning.....	Self extinguished
Weight.....	38.9 lbs. per square	Average Extent Of Burning.....	2.379 mm
Warpage.....	0.00"	Weathering.....	Passes per ASTM D1435 & D3679
Heat Shrinkage.....	0.3%	Windload Rating*.....	162 MPH
		*(Wind Velocity based on IBC)	



Style Crest, Inc.
 2450 Enterprise St.
 Fremont, Ohio 43420
www.rmcsiding.com

Made in the U.S.A. by America's dedicated workforce.
 Printed in the U.S.A. Specifications are subject to change without notice.

ProPride Data

062510 © Copyright 2010



GREEN APPROVED

RMC Siding™ and Soffit
 Certificate #00099